

Product Information



PREVent-G Shrinkage Compensating Admixture

Description: Shrinkage compensating admixture for cementitious mixes needing crack control.

Typical Properties:

Appearance	Free-flowing powder, off-white to light brown	
Density	Loose bulk density (lb/ft ³)	45
	Tapped bulk density (lb/ft ³)	54
pH (10% aqueous slurry)	10-11	
Specific Gravity	2.252	

Product Application:

PREVent-G is a specially-formulated powder concrete admixture designed to reduce shrinkage cracking as well as curing. The admixture is designed for use in the following applications:

- All types of cement-based mixes, cast-in-place, precast, prestressed, mortars and grouts, as well as pre-packaged cement-based mixes.
- Both straight cement mixes and in blended cement mixes.
- Watertight concrete structures such as WTP, WTP, dams and reservoirs.
- Architectural and decorative concrete to improve aesthetics.
- Concrete floors to control shrinkage cracking and extend joint spacing.
- Concrete structures exposed to de-icing chemicals and chloride exposure, such as bridge decks (full-depth and partial overlays), parking structures, and marine structures.
- Any highly-restrained structure.
- Mass concrete.
- Thin concrete sections and overlays.

Benefits:


- Significantly reduces shrinkage cracking caused by drying and autogenous shrinkage.
- Improves durability.
- Decreases curling and related cracks.
- More economical than alternative SRAs.
- Allows for reduced usage of control joints.
- Reduces infiltration of water, salt and aggressive chemicals by reducing cracks.

Dosage Rates: Typical PREVent-G addition rates range from 2-7%, based on cement content, or 2-7 lbs for each 100 lbs of cement in concrete, mortar or grout.



PREvent-G Data Sheet

www.premiercpg.com
1-800-227-4287



Usage: PREvent-G should be added to the concrete either simultaneously with the other powder components or after all of the other ingredients are in the truck. If added at the end of the load, adequate mixing must be ensured.

When trial mix designs are performed for mix approval, ensure that sample materials used for the trial are representative of the actual production materials.

PREvent-G is not designed to replace proper curing procedures. TO PREVENT DRYING SHRINKAGE, ENSURE THAT PROPER CURING IS PROVIDED WHEN PLACING CONCRETE.

Packaging: PREvent-G is available in 50-lb lined bags and 1,000- and 2,000-lb lined bulk sacks. Bulk truckload or railcar delivery is available upon request.

Handling and Storage: Store in a dry, protected place. The product is stable under normal conditions of dry storage. Do not allow water to get inside containers. Exposed, unprotected material will absorb moisture and carbon dioxide from the air. Appropriate personal protective equipment should always be worn when handling material. See MDS for more information.

300 Barr Harbor Drive, Suite 250, West Conshohocken, PA 19428
T: 800-227-4287 www.premiercpg.com

rev 01302015

PRODUCT WARRANTY: Premier warrants that its Products shall be free from defects in material and workmanship and shall substantially conform to Premier's Product specifications upon shipment. If Buyer believes this warranty has been breached, it will provide written notice to Premier as soon as the defect becomes apparent, but no later than six (6) months from the date of shipment. If during the warranty period the Products are found to be defective in material or workmanship or fail to substantially conform to Premier's Product specifications, Premier will furnish replacement Products, ex-works jobsite, or at Premier's option, refund the purchase price, provided the Buyer has stored and installed the Products in accordance with Premier's instructions and provided further that Premier is given the opportunity to inspect and test the Products within fifteen (15) days from when the defect becomes apparent and is given access to all necessary operating records with respect to the use of the Products. THE EXPRESS WARRANTY SET FORTH IN THIS ARTICLE IS EXCLUSIVE, AND NO OTHER WARRANTIES OF ANY KIND, WHETHER STATUTORY, ORAL, WRITTEN, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, SHALL APPLY. THE BUYER'S EXCLUSIVE REMEDIES AND PREMIER'S ONLY OBLIGATIONS ARISING OUT OF OR IN CONNECTION WITH DEFECTIVE MATERIAL OR WORKMANSHIP, WHETHER BASED ON WARRANTY, CONTRACT, TORT (INCLUDING NEGLIGENCE) OR OTHERWISE, SHALL BE THOSE STATED HEREIN.

LIMITATION OF LIABILITY: The liability of Premier, its agents, employees, subcontractors and suppliers with respect to any and all claims arising out of the performance or nonperformance of obligations in connection with the design, manufacture, sale, delivery, storage, installation or use of the Products or the rendition of services, whether based on contract, warranty, tort (including negligence), strict liability or otherwise, shall not exceed the Contract Price and shall in no event include damages for loss of profits or revenue or the loss of use of either; loss by reason of plant shutdown or inability to operate at rated capacity; increased expense of operation of plant or equipment; increased costs of purchasing or providing equipment, materials, supplies or services outside of Seller's scope of supply; or incidental or consequential damages of any nature. No such claims shall be asserted against Seller, its agents, employees, subcontractors or suppliers, unless the injury, loss or damage giving rise to the claims is sustained prior to the expiration of the period of warranty specified herein, and no suit or action thereon shall be instituted or maintained unless it is filed in a court of competent jurisdiction within one (1) year after the date the cause of action accrues. This LIMITATION OF LIABILITY Article shall apply to and prevail over any and all provisions contained in any of the documents comprising the Contract.

For orders or technical questions, contact Premier CPG Customer Service at 1-800-227-4287, or your local distributor.